

1. Product and Company Identification

Material name SEALANT 18X-FG
Version # 00
Issue date 01-18-2013
Revision date 01-18-2013
Supersedes date -
Chemical name Polyolefin Resin
Chemical description Fibrous Resin Mixture
CAS # Mixture
Product code 800-0044
Product use Industrial Leak Sealant
Manufacturer information
Manufacturer/Supplier Team Industrial Services, Inc.
 200 Hermann Drive, Alvin, Texas 77511
Emergency Contact CHEMTREC - 24 HOURS
 USA: CHEMTREC: 800-424-9300
 International: 703-527-3887 (Collect)

2. Hazards Identification

Physical state Liquid.
Appearance Black pliable semi-solid with solvent odor.
Emergency overview WARNING
 Combustible liquid.
 Harmful if swallowed. Causes skin and eye irritation. Vapors may cause drowsiness and dizziness. May adversely affect the developing fetus.
OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects
Routes of exposure Eye contact. Ingestion. Inhalation. Skin contact.
Eyes May cause eye irritation.
Skin May cause skin irritation. Prolonged or repeated contact may dry skin and cause dermatitis. The product contains organic solvents which may be absorbed into the body by skin contact and cause permanent damage to the nervous system, including the brain.
Inhalation Vapors may cause drowsiness and dizziness. When cured: Elevated temperatures or mechanical action may form dust and fumes which may be irritating to mucous membranes and respiratory tract. Inhalation of high concentrations of quartz dust can lead to the lung disease known as silicosis, with cough and shortness of breath. Prolonged breathing of high levels of crystalline silica can cause silicosis. Also, airborne crystalline silica is possibly carcinogenic to humans.
Ingestion Harmful if swallowed. Components of the product may be absorbed into the body by ingestion.
Target organs Central nervous system. Eyes. Skin.
Chronic effects May adversely affect the developing fetus based on animal data. Danger of serious damage to health by prolonged exposure. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material.
Signs and symptoms Skin irritation. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing. Shortness of breath.
Potential environmental effects Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Polymer	25034-71-3	50-80

Components	CAS #	Percent
Graphite	7782-42-5	25-50
Dicumyl peroxide	80-43-3	5-10
Toluene	108-88-3	5-10
Carbon fiber	7440-44-0	1-5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

First aid procedures

Eye contact	Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Skin contact	Remove contaminated clothing and shoes. Flush thoroughly with water for at least 15 minutes. If irritation occurs, get medical assistance.
Inhalation	Move to fresh air. Get medical attention if any discomfort occurs.
Ingestion	Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Get medical attention immediately.

Notes to physician Treat symptomatically.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

Flammable properties The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. Intensive heat and fire may release toxic and corrosive gases.

Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	No restrictions known.

Protection of firefighters

Specific hazards arising from the chemical	Solvent vapors may form explosive mixtures with air. By heating and fire, corrosive vapors/gases may be formed.
Protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire fighting equipment/instructions In the event of fire, cool tanks with water spray. Move containers from fire area if you can do it without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

Hazardous combustion products Carbon oxides. Silicon oxides.

6. Accidental Release Measures

Personal precautions Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Wear appropriate protective equipment and clothing during clean-up. See Section 8 of the MSDS for Personal Protective Equipment.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods for containment Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. After removal flush contaminated area thoroughly with water. This material and its container must be disposed of as hazardous waste.

Never return spills to original containers for re-use.

7. Handling and Storage

Handling

Pregnant or breastfeeding women must not handle this product. Avoid inhalation of vapors and contact with skin and eyes. The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. Ground container and transfer equipment to eliminate static electric sparks. Use non-sparking tools and explosion-proof equipment. Use only with adequate ventilation. Wear approved safety goggles. Wear protective gloves and appropriate clothing to prevent skin contact. Avoid generation and spreading of dust. Observe good industrial hygiene practices.

Storage

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
Toluene (CAS 108-88-3)	TWA	20 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Graphite (CAS 7782-42-5)	TWA	15 millions of particle

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable.
Toluene (CAS 108-88-3)	TWA	188 mg/m ³	
		50 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable.
Toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
Toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable dust.
Toluene (CAS 108-88-3)	TWA	188 mg/m ³	
		50 ppm	

Mexico. Occupational Exposure Limit Values

Components	Type	Value
Graphite (CAS 7782-42-5)	TWA	10 mg/m ³
Toluene (CAS 108-88-3)	TWA	188 mg/m ³ 50 ppm

Engineering controls Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors.

Personal protective equipment

Eye / face protection Wear approved safety goggles.

Skin protection Wear protective gloves. Polyvinyl alcohol gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier. Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and working clothes should be kept separately.

9. Physical & Chemical Properties

Appearance Black pliable semi-solid with solvent odor.

Physical state Liquid.

Form Pliable semi-solid.

Color Black.

Odor Solvent.

Odor threshold 0.5 - 23 ppm (Toluene).

pH Not available.

Vapor pressure 6.0 mm Hg @ 68 F

Vapor density Not available.

Boiling point > 230 °F (> 110 °C)

Melting point/Freezing point Not available.

Solubility (water) Negligible.

Specific gravity 0.9

Flash point 198 °F (92.2 °C) Closed Cup

Flammability limits in air, upper, % by volume Not available.

Flammability limits in air, lower, % by volume Not available.

Auto-ignition temperature 896 °F (480 °C) (Toluene)

Evaporation rate 1 (Butyl acetate=1)

Other data

Flash point class Combustible IIIA

10. Chemical Stability & Reactivity Information

Chemical stability Material is stable under normal conditions.

Conditions to avoid Flames and sparks.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides. Silicon oxides.

Possibility of hazardous reactions Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

Components	Species	Test Results
Graphite (CAS 7782-42-5)		
Acute		
<i>Oral</i>		
LD50	Rat	> 10000 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	14.1 ml/kg
<i>Inhalation</i>		
LC50	Rat	49000 mg/m ³ , 4 Hours
<i>Oral</i>		
LD50	Rat	636 mg/kg
Sensitization	Not a skin sensitizer.	
Acute effects	Harmful if swallowed. Vapors may cause drowsiness and dizziness.	
Local effects	Causes skin and eye irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Components of the product may be absorbed into the body by inhalation, ingestion and through the skin.	
Chronic effects	Danger of serious damage to health by prolonged exposure. Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. When cured: Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material.	
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure. When cured: Prolonged breathing of high levels of crystalline silica can cause silicosis. Also, airborne crystalline silica is possibly carcinogenic to humans.	
ACGIH Carcinogens		
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Epidemiology	None known.	
Mutagenicity	Not available.	
Neurological effects	May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue) and/or damage.	
Reproductive effects	May adversely affect the developing fetus based on animal data.	
Teratogenicity	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.	
Symptoms and target organs	Skin irritation. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing. Shortness of breath.	
Further information	When cured: Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material.	

12. Ecological Information

Ecotoxicological data

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
		5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)
		5.5 mg/l, 96 hours
Ecotoxicity	Harmful to aquatic life with long lasting effects.	
Environmental effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.	
Persistence and degradability	The product contains inorganic compounds which are not biodegradable.	

Bioaccumulation / Accumulation	No data available on bioaccumulation.
Partition coefficient Toluene (CAS 108-88-3)	2.73
Mobility in environmental media	The product contains substances which are insoluble in water and which sediment in water systems. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

13. Disposal Considerations

Waste codes	Not regulated.
Disposal instructions	Dispose of this material and its container to hazardous or special waste collection point. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

DOT	Not regulated as a hazardous material by DOT.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
TDG	Not regulated as dangerous goods.

15. Regulatory Information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	Toluene (CAS 108-88-3)
US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration	Toluene (CAS 108-88-3) 1.0 %
US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance	Toluene (CAS 108-88-3) Listed.
CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)	Toluene: 1000
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
Section 302 extremely hazardous substance (40 CFR 355, Appendix A)	No
Section 311/312 (40 CFR 370)	Yes
Drug Enforcement Administration (DEA) (21 CFR 1308.11-15)	Not controlled
Canadian regulations	This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS status Controlled
WHMIS classification B3 - Combustible Liquids
 D2A - Other Toxic Effects-VERY TOXIC
 D2B - Other Toxic Effects-TOXIC

WHMIS labeling



Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Graphite (CAS 7782-42-5) Listed.
 Toluene (CAS 108-88-3) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Toluene (CAS 108-88-3) Listed.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991 Developmental toxin.

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009 Female reproductive toxin.

US - New Jersey RTK - Substances: Listed substance

Graphite (CAS 7782-42-5) Listed.
 Toluene (CAS 108-88-3) Listed.

US. Massachusetts RTK - Substance List

Graphite (CAS 7782-42-5) Listed.
 Toluene (CAS 108-88-3) Listed.

US. New Jersey Worker and Community Right-to-Know Act

Toluene (CAS 108-88-3) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

Graphite (CAS 7782-42-5) Listed.
 Toluene (CAS 108-88-3) Listed.

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.
 I - Safety Glasses, Gloves, Dust, Vapor Respirator

HMIS® ratings Health: 2*
 Flammability: 2
 Physical hazard: 0
 Personal protection: I

NFPA ratings Health: 2
 Flammability: 2
 Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.